

Instructions for Installation of the VLX (VT-600) Sissy Bar Kit (#RON-3861.1)

Be sure to contact us at Tech Support (support@ScootWorks.com) if you have *any* questions about this installation!

UNPACKING!

The shipping container and contents must be inspected by the purchaser for damage to goods immediately upon receipt of goods, and a claim must be filed with the carrier if damage is discovered. The purchaser must contact Scootworks within 24 hours from receipt of damaged goods to file a claim, and for further instructions. Your Scootworks Honda VLX (VT-600) sissy bar kit should contain the following parts:

- #1- 2 mounting rails
- #2- 4 screws 6x25mm
- #3- 4 spacers 9mm
- #4- 4 washers 6mm
- #5- 4 6mm lock washers
- #6- 4 6mm nuts
- #7- 4 8x25 bolts
- #8- 4 8mm lock washers
- #9- 4 8x20mm bolts
- #10- 4 8mm lock washers
- #11- 4 8mm nuts
- #12- 1 Sissy bar with pad
- #13- 4 Mounting tabs

BEGIN INSTALLATION...

1. Remove the seat from your motorcycle by removing the 2 screws under the middle of your seat. There is one screw on each side. If there has never been a sissy bar installed on your bike, it may be necessary to drill holes in the fender in which to mount the sissy bar in the space made available by Honda. Consult your maintenance manual for more information regarding this procedure.
2. Attach the mounting rails to each side of the sissy bar. Use the (4) 8 x 20mm screws, (4) lock washers, flat washers and locking nuts to secure the mounting rails to the sissy bar. (If you are also installing the luggage rack, install the luggage rack on the inside of the mounting rails) See the photo on the next page (fig. 2).
3. Attach the (4) mounting tabs to the inside of the rails with the bend of the mounting tab pointed downwards. Use the (4) 8mm socket head bolts and 8mm flat washers to secure the mounting tabs to the rails. See photo below (fig. 1).



(Fig.1)

4. Insert the flat head screws into the mounting tabs, followed by the spacers. See photo above.
5. Place the sissy bar assembly on the motorcycle and bolt the (4) screws on the sissy bar onto the motorcycle. Use the 8mm locking washers and nuts under the fender and tighten. The assembled sissy bar should look like the photo below.



(Fig.2)

6. Replace the seat on the motorcycle and tighten the screws. This is a good time to take some photos of your bike to send to us and your friends! Send your photos to webmaster@scootworks.com and we'll put it in the "Photo Gallery" section of our website.
7. As with any proper maintenance program, you should periodically check all bolts on your motorcycle to ensure they are properly tightened. Keep the beautiful finish on your new sissy bar with Flitz chrome polish and sealant, available at Scootworks.